



Document Title:
Repair Sleeve for ACSS Conductor

Document Type:
Specification

Document No.:
4751.50.006

Department:
Transmission Engineering

For others, specify here

Version:
01

Effective Date:
Oct 9, 2025

Shared document with: N/A

** Select the Departments impacted by the document (If apply)*

For others, specify here

Author

Rodolfo A. Flores Ortiz, PE (Lic. 27131)
Senior Engineer, Distribution Standards & Materials

Signature and Date:

Oct 7, 2025

Reviewer

Miguel J. Rios López, PE (Lic. 16636)
General Engineer, Distribution Standards & Materials

Signature and Date:

Oct 7, 2025

Reviewer

Oscar Venegas, PE (Lic. 23125)
Supervisor, Line Engineering Standards

Signature and Date:

Oct 7, 2025

Approver

Reinaldo Baretty Huertas, PE (Lic. 16712)
Director Systems Standards and Records

Signature and Date:

Oct 9, 2025

Management Approval (If apply)

Approver

Name
Position

Signature and Date:

Related/Referenced Documents

N/A

Version History

Version	Date	Revision
01	Oct. 07, 2025	Initial release for 002-87773, 002-87774, and 002-87775.

Item Version History

Warehouse Catalog #	Asset Suite #	Version	Date
002-87773	87773	1	10/07/2025
002-87774	87774	1	10/07/2025
002-87775	87775	1	10/07/2025

Table of Contents

1. Introduction.....	4
2. Special Requirements.....	4
3. Literature	4
4. Compatible with	5
5. Markings.....	5
6. Packaging.....	5
7. Number Per Package (Logistics).....	5
8. Acceptance Criteria.....	5
9. Description	6
10. Inspection.....	6
11. Proposal Information	6
12. Table 1: Warehouse and Asset Suite Identification Number.....	7
Appendix.....	8
Appendix 1: Table of Compliance	9



1. Introduction

This is a general specification that covers the minimum requirements for repair sleeve for ACSS to be used in the transmission system in Puerto Rico. Further information will be provided by LUMA Energy at the time of order placement and will provide information on site specific conditions, quantity, and other requirements. This document includes the general characteristics of the product.

2. Special Requirements

Samples shall be furnished as requested by LUMA Energy. Vendors that have supplied this product to LUMA on previous orders will not have to furnish samples at bid opening. The product will be received at LUMA's general warehouse (017) at Palo Seco, Puerto Rico. Shipping will include transportation and unloading at the indicated warehouse.

3. Literature

- 3.1. Descriptive and technical literature must be supplied by the vendor at time of bidding. This literature must include, but is not limited to, details of material, drawings, documented testing, and instructions for use and installation. **The literature must be an official document from and certified by the manufacturer.** Failure to submit documents on time and duly certified by the manufacturer will cause bidder disqualification.
- 3.2. If required by LUMA, final drawings and documentation shall be submitted by the vendor before the manufacturing and shipping process for approval.

4. Compatible with

For compatible manufacturer and model see Table 1. These models are examples of the product described in this document and do not represent a preference. LUMA will evaluate equally any model not listed here during any acquisition event.

5. Markings

- 5.1. Containers shall be marked outside with LUMA Energy's purchase order and item number.
- 5.2. Individual package(s) shall be clearly marked with manufacturer name and item information (part number, serial number, quantity, etc.).
- 5.3. Packaging labels and tags shall be waterproof.

6. Packaging

- 6.1. All products shall be packaged and marked in such a way as to facilitate handling and protection from damage and that the receiving warehouse can readily identify it and send it, in one complete unit, to a field location without opening crates or boxes to sort items and/or parts.
- 6.2. A list of all parts included in the container and/or package must be provided at delivery time so the receiving personnel can verify that everything requested is present, avoiding any delay in the receiving process.

7. Number Per Package (Logistics)

Standard package: One (1) unit per package or as requested by LUMA.

8. Acceptance Criteria

- 8.1. Test required: certified by external qualified laboratories.
- 8.2. Product shall be manufactured in accordance with the latest issue below (section 8.3). When conflicts occur between purchaser's specifications and the latest issue below, the purchaser's specification shall prevail.

- 8.3. Latest applicable codes, standards, and other regulations (ANSI, ASTM, NEMA, etc.).
- 8.4. If any other standards different from the ones indicated in this document are used, the supplier must provide information showing compatibility with the required ones.

9. Description

- 9.1. ACSS repair sleeve is used to restore the conductor to 95% of its rated strength when there is minor damage to the conductor.
- 9.2. Shall be compatible with high temperature ACSS conductors (250°C = 482°F). Refer to Table 1 for specific conductor compatibility requirements.
- 9.3. Material shall be aluminum.
- 9.4. Repair sleeve shall be an assembly containing two semi cylindrical pieces with an interlocking key.
- 9.5. Length before compression shall be as specified in Table 1.
- 9.6. Shall be compatible with die size as specified in Table 1. Shall be compatible with standard tooling Y60 compression tool.

10. Inspection

- 10.1. Upon inspection of incoming products, the purchaser reserves the right to refuse their shipments and to determine the acceptability or rejection of the product received. The supplier shall be liable for all costs incurred for a product that is rejected.
- 10.2. The acceptance of any product shall in no way relieve the vendor from his responsibility to meet all the requirements of this specification, and it would not prevent subsequent rejection if such products were found later to be defective or out of compliance.

11. Proposal Information

- 11.1. Submitted proposals must include:
 - a. Technical information, drawings, and tests.

b. Table of Compliance completed by the bidder with reference (see Appendix 1).

12. Table 1: Warehouse and Asset Suite Identification Number

Warehouse Catalog #	Asset Suite #	Conductor Size (Strands) (Strength)	Min. Length before compression	Conductor OD	Die Index	Compatible Manufacturer & Model
002-87773	87773	266.8 (26/7) ACSS	18"	0.642	76AH	AFL 5276.3HT
002-87774	87774	556.5(24/7) ACSS	24"	0.914"	24AH L722	AFL 5224.3HT Burndy YNU39RHT
002-87775	87775	795 (26/7) ACSS	24"	1.107"	30AH L725	AFL5230.3HT Burndy YNU451RHT

- End of Specification -

Appendix

Appendix 1: Table of Compliance

Line	Description	Pass/Fail (P / F)	Comments
1	Compliance with the document 4751.50.006		
2	Complies with applicable industry standards.		
3	Tech. info. and drawings provided.		
4	ACSS repair sleeve		
5	Compatible with high temperature ACSS conductors (250°C).		
6	Material: Aluminum		
7	Assembly containing two semi cylindrical pieces with an interlocking key.		
8	Length before compression shall be as specified in Table 1.		
9	Shall be compatible with die size as specified in Table 1. Compatible with standard Y60 compression tool.		

NOTE: This table is only a checklist for reference. The compliance must be with the complete document. Filling out the table with “PASS” won’t be accepted as a compliance without the technical information required to certify it.












4751.50.006 ACSS Repair Sleeve (10-07-2025)


Final Audit Report

2025-10-09


Created:	2025-10-07
By:	Rodolfo Flores (rodolfo.floresortiz@lumapr.com)
Status:	Signed
Transaction ID:	CBJCHBCAABAAnxkSYkG3uuvH7EvlH7zYXamYxbMIG_ho

"4751.50.006 ACSS Repair Sleeve (10-07-2025)" History

-  Document created by Rodolfo Flores (rodolfo.floresortiz@lumapr.com)
2025-10-07 - 5:51:02 PM GMT
-  Document emailed to Rodolfo Flores (rodolfo.floresortiz@lumapr.com) for signature
2025-10-07 - 5:51:07 PM GMT
-  Document e-signed by Rodolfo Flores (rodolfo.floresortiz@lumapr.com)
Signature Date: 2025-10-07 - 5:51:44 PM GMT - Time Source: server
-  Document emailed to Miguel Rios (miguel.rioslopez@lumapr.com) for signature
2025-10-07 - 5:51:46 PM GMT
-  Email viewed by Miguel Rios (miguel.rioslopez@lumapr.com)
2025-10-07 - 5:52:38 PM GMT
-  Document e-signed by Miguel Rios (miguel.rioslopez@lumapr.com)
Signature Date: 2025-10-07 - 5:53:00 PM GMT - Time Source: server
-  Document emailed to Oscar Venegas (oscar.venegas@lumapr.com) for signature
2025-10-07 - 5:53:02 PM GMT
-  Email viewed by Oscar Venegas (oscar.venegas@lumapr.com)
2025-10-07 - 5:53:50 PM GMT
-  Document e-signed by Oscar Venegas (oscar.venegas@lumapr.com)
Signature Date: 2025-10-07 - 5:54:59 PM GMT - Time Source: server
-  Document emailed to Reinaldo Baretty (reinaldo.baretty@lumapr.com) for signature
2025-10-07 - 5:55:01 PM GMT
-  Email viewed by Reinaldo Baretty (reinaldo.baretty@lumapr.com)
2025-10-09 - 8:46:31 PM GMT

 Document e-signed by Reinaldo Baretty (reinaldo.baretty@lumapr.com)

Signature Date: 2025-10-09 - 8:47:19 PM GMT - Time Source: server

 Agreement completed.

2025-10-09 - 8:47:19 PM GMT